

SEMI-RECESSED BOTTLE FILLER

Mounted mains-connected bottle fillers

Our semi-recessed bottle fillers offer refrigerated drinking water with automatic dispensing.



KEY FEATURES

- Electronic touch free activation (AC-MWSM8EBFY-ASM) with hands free activation with shut off timer
- Built in bottle counter, filter monitor and programmable timeout feature
- Large alcove to fit most sports bottles
- Energy-efficient LED's illuminate alcove and aids bottle filling
- Built in drain - no drip tray to empty
- Heavy-duty steel frame with a stainless steel finish
- Space saving surface mount frame assembly
- Integrated bottle counter and filter monitor
- Built-in 100-micron strainer stops particles before they enter the waterway
- Waterways are lead-free in materials and construction
- High efficiency cooling system and refrigerant R-134a
- Built-in panel locks for easy access to chiller and filtration
- A wall cavity is required behind the bottom half to fit the chiller



Semi-Recessed Bottle Filler units offer refrigerated drinking water with automatic, hands-free dispensing mechanisms. Featuring a 100-micron strainer to stop particles entering the lead-free waterway and a heavy-duty galvanised steel frame making the unit extra durable. Perfect for high volume applications. All refrigerated fountains use R-134a refrigerant and have an efficient, high-performing refrigeration system.

All Oasis bottle fillers are made with proprietary Freshfield technology. Freshfield harnesses the natural bacteria-fighting power of silver by infusing it into a poly compound on moulded parts of the alcoves.

Model Information (AC-MWSM8EBFY-ASM)

Activation	Contactless (Infrared Sensor)
Sensor Coverage	Up to 5cm (approx.)
Filtration	Filter (optional), Built-in 100 micron strainer
Water Connections	Inlet: 1/2" BSP connector, Drain: 40mm Female Socket (Not trapped)
Exterior	Antimicrobial ABS Plastic, Brushed Stainless Steel
Chassis	Heavy Duty Galvanised Steel
Dimensions	1051(H) x 530(W) x 150(D)
Alcove Height	265mm
Net Weight	35kg
Power Supply	220-240V, 50/60 Hz
Cooling Performance	30 LPH - Rated Capacity & Base Rate - (10°C in 21°C amb. temp.)
Full Load Amps	2.2 A
Rated Watts	347 W
Country of Origin	Mexico
Certifications	WaterMark, ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS)
Warranty	1 Year Full, 2 Years Parts Only

Your Partner in Cool.

**AQUA
COOLER**

TECHNICAL DRAWINGS

AC-MWSM8EBFY-ASM

