



GENERAL INFO

SEDIMENT REMOVAL CARTRIDGE

Ribbed Sediment Cartridges

Puretec RB Series cartridges use grooves to increase surface area for greater dirt-holding capacity. These cartridges reduce dirt, rust, algae and organic matter.

FEATURES & BENEFITS

- Graded density ribbed design for longer life
- Available in 5, 25 and 50 microns
- Flow rates up to 166 litres/minute
- Large surface area from ribbed design gives longer service life
- Maximum temperature at 60°C

MATERIALS OF CONSTRUCTION

- Filter Media: Polypropylene
- Temperature Rating: 32°F to 140°F (0°C to 60°C)

HOUSING SPECIFICATIONS AND PERFORMANCE DATA

Model	Micron Rating	Size	Min/Max Temp	Min/Max Pressure	Min/Max Flow (Lpm)
RB051	5	standard 2.5" x 10"	0 - 60 °C	100-900 kPa	0 - 28
RB251	25	standard 2.5" x 10"	0 - 60 °C	100-900 kPa	0 - 35
RB501	50	standard 2.5" x 10"	0 - 60 °C	100-900 kPa	0 - 38
RB051-2	5	standard 2.5" x 10" (Twin Pack)	0 - 60 °C	100-900 kPa	0 - 28
RB501-2	50	standard 2.5" x 10" (Twin Pack)	0 - 60 °C	100-900 kPa	0 - 38
RB05MP1	5	MaxiPlus™ 4.5" x 10"	0 - 60 °C	100-900 kPa	0 - 76
RB25MP1	25	MaxiPlus™ 4.5" x 10"	0 - 60 °C	100-900 kPa	0 - 85
RB05MP2	5	MaxiPlus™ 4.5" x 20"	0 - 60 °C	100-900 kPa	0 - 156
RB25MP2	25	MaxiPlus™ 4.5" x 20"	0 - 60 °C	100-900 kPa	0 - 166