



GENERAL INFO

REMOVES TASTE, ODOUR, CHLORINE AND CHEMICALS

Granular Carbon Cartridges

The Puretec GC Series granular carbon cartridges effectively remove unwanted taste, odour, chlorine, volatile chemicals and pesticides leaving beautiful tasting clear water for all drinking water applications. They are designed to allow maximum contact between the water and carbon, ensuring maximum absorption.

The construction of the cartridge allows water to enter at one end and pass through the entire length of the carbon bed before exiting to the other end of the cartridge, while an external expansion pad minimises channelling or bypass. Before the water exits the cartridge, a 20 micron post-filter helps remove carbon fines and other suspended particles from the filtered water. The post-filter is permanently fastened to an innovative support basket, ensuring that it is firmly secured and eliminating any potential of bypass, making it suitable for drinking water, food service, whole house filtration and many other situations.

The Puretec GC Series cartridges are available in variety of sizes and flow rates, and effectively provide good general-purpose drinking water filtration. Additional models that include fluoride removal, heavy metal removal or scale control are also available.

MATERIALS OF CONSTRUCTION

- Filter Media Granular Activated Carbon
- End Caps Polystyrene
- Post-filter Spun Polypropylene
- Outer Casting Polystyrene
- Expansion Pad Polypropylene
- Gaskets Buna-N (top)
Santoprene (bottom)

FEATURES & BENEFITS

- Highly effective taste, odour, chlorine, chemical and sediment removal.
- 3 times the capacity of similar cartridges.
- Designed for maximum absorption.

FOR MAINS AND FRESH WATER ONLY

Note: This specification sheet has been designed to help make product selection easy. However due to the complex nature of water chemistry, we strongly encourage confirming any product selection with one of our team. We may need to perform a water analysis test to confirm contaminants in water. ^Removes indicates significant reduction, not necessarily 100% removal

For more information contact your local stockist or visit us at puretecgroupp.com
Australia **1300 140 140** | New Zealand **0800 130 140**

CARTRIDGE SPECIFICATIONS AND PERFORMANCE DATA

	Model	Dimensions	Description	Micron Rating (Nominal)	Flow (Lpm)
5"	GC205	standard 2.5" x 5"		20 post-filter	7
9"	GC059	standard 2.5" x 9"		5 post-filter	11
10"	GC051	standard 2.5" x 10"		5 post-filter	13
	GC051-SL	slimline 2.5" x 10"	Scale control	5 post-filter	11
	GC201-H	standard 2.5" x 10"	Heavy metal reduction	20 post-filter	15
20"	GC202	standard 2.5" x 20"		20 post-filter	27
10" MP	GC20MP1	MaxiPlus™ 4.5" x 20"		20 post-filter	32
20" MP	GC20MP2	MaxiPlus™ 4.5" x 20"		20 post-filter	40

Temperature Rating : 40°F to 125°F (4.4°C to 51.7°C).

